

IMAGETEAM 3800

Hand Held Linear Imager



Description

Introducing the IMAGETEAM 3800, a high performance, hand held bar code scanner. The IT3800 uses linear imaging technology to set a new standard for hand held scanners by combining a bright, sharp aiming line with high resolution imaging to deliver exceptional reading performance.

The IT3800 handle is smoothly contoured to fit all sized hands, plus has a soft grip area to add comfort and prevent slipping. Its aesthetically pleasing look surrounds a rugged, durable construction, built for demanding work environments.

Each decoded output scanner has the capability to connect as a keyboard wedge, use the serial port, output non decoded laser compatible signals, or operate in wand emulation mode. The IT3800 connects to all popular PCs and many specialty terminals and portable data terminals. A non decoded mode can be used with external wedge decoders and portable terminals or other devices with decoding capability. Standard cables are used to reduce replacement expense.

Features

Bright, Sharp and Focused Aiming Line

Solid, Rugged Design

New Design

Powerful, Flexible Architecture

Increased Reading Distances

Real World Reading Performance

Benefits

- Intuitively easy to aim and scan codes in any lighting condition from darkness to full sunlight.

- Easy to scan tightly stacked bar code sheets or small, high resolution labels.

- No moving parts inside and solid construction outside deliver years of reliable service in demanding work environments.

- Attractive styling compliments most existing POS environments, while user comfort is enhanced by the smooth handle curves, soft molded grip area, and comfortable trigger.

- Connects and interfaces to all major PCs and terminals easily and quickly with Windows™ based programming tools or bar code programming menus. Multiple interfaces are included in each scanner to simplify end user inventory and provide connectivity in multiple applications within a site.

- Easily covers the full range of hand held scanning uses in point of sale and general purpose scanning applications.

- Accommodates printer induced bar space variation, faded labels, short quiet zones, low contrast codes, dot matrix printing, and multi part forms with higher resolution, better optics and improved decoding algorithms.

The IT3800 is excellent in hand held scanning applications such as retail point of sale and in-store inventory. It operates from a tabletop holder in manual trigger mode, or may be placed in an adjustable stand for automated operation. The IT3800 can be used indoors or outside in bright sunlight. Typical applications are retail point of sale, in-store inventory, document management, transaction processing of bar coded receipts, payment counter, outdoor sales kiosks, and reading of vehicle registrations.

Specifications

Performance

Illumination:	630 NM Visible Red LED
Receiving Device:	3648 element linear imager
Reading Distance:	From 1 in. (2.5 cm) to 8 in. (20.3 cm) on medium density codes
Reading Width:	5 in. (12.7 cm) code width at 7 in. (17.8 cm) distance
Resolution:	5 mil. at 3.5 in. (8.8 cm) distance
Skew Angle:	$\pm 30^\circ$
Pitch Angle:	$\pm 15^\circ$
Horizontal Velocity:	5 in. (12.7 cm) per second
Minimum Reflectance Difference:	30%
Scan Rate:	Programmable to 270 scans per second
Decode Rate:	270 decodes per second

Mechanical/Electrical

Dimensions

Length:	5.3 in. (13.5 cm)
Height:	6 in. (15.2 cm)
Width:	3.1 in. (7.9 cm)
Weight:	6.3 oz. (179.2 g)
Housing:	Polycarbonate/ABS blend, UL 94V0

Power Requirements: 5Vdc \pm 10% at scanner

Current Draw:	<u>Scanning</u>	<u>Standby</u>	<u>Low Power</u>	<u>In-Rush</u>
@ 270 s/s	275mA	125mA	5 microA	300mA
@ 67 s/s	150mA	125mA	5 microA	300mA

Power Supply

Noise Rejection: Maximum 100mV peak to peak, 10 to 100 kHz

Environmental

Temperature

Operating: +32°F to +122°F (0°C to +50°C)

Storage: -40°F to 140°F (-36°C to +60°C)

Humidity: 0 to 95%

Mechanical Shock: Operational after 25 drops from 5 ft. (1.53 m) to concrete

Ambient Illumination: 0 - 100,000 lux

ESD Protection: Functional after 15kV discharge

Vibration: Withstands 5G peak from 20 to 300 Hz

Agency: FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, TÜV

Symbologies: Codabar, Code 3 of 9 including PARAF, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, Code 11, Code 128, UPC, EAN/JAN, China Postal Code.

Interfaces: All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, TTL level RS-232, wand emulation mode, and includes (HHLC) non decoded laser compatible output.

Warranty: Three year factory warranty.

Main Office

4619 Jordan Road
Skaneateles Falls, NY 13153-0187
Tel: (315) 685-8945
Fax: (315) 685-3172

European Office

Welch Allyn Ltd.
Block 1, Bracken Business Park
Sandyford,
Co Dublin
Ireland
Tel: Int+353-1-216-0070
Fax: Int+353-1-295-6353

U.K. Office

Welch Allyn U.K. Ltd.
Dallam Court
Dallam Lane
Warrington
Cheshire WA2 7LT
United Kingdom
Tel: Int+44 1925 240055
Fax: Int+44 1925 631280

Asia/Pacific Office

10/F, Tung Sun Commercial Centre
194-200 Lockhart Road
Wanchai, Hong Kong
Tel: Int+852 2511 3050/2511 3132
Fax: Int+852 2511 355

Japan Office

Bon Marusan 8F
3-5-1 Kanda-Jinbocho
Chiyoda-ku
Tokyo 101, Japan
Tel: Int+81 3 5212 7392
Fax: Int+81 3 3261 7372

Latin America Office

5150 North Tamiami Trail
Suite 302
Naples, FL 34103-2821
Tel: (941) 263-7600
Fax: (941) 263-9689

Web Site Address

dcd.welchallyn.com

©1998, Welch Allyn, Inc.
All rights reserved.

Printed in the U.S.A.

Due to Welch Allyn's continuing product improvement programs, specifications and features herein are subject to change without notice.